

Item	Unit	Type: HM-T-GJ							
		0.08mm	0.09mm	0.10mm	0.11mm	0.12mm	0.13mm	0.14mm	0.15mm
Appearance	----	scar&hole, broken&folded, patched place							
Width	MM	4.5---880							
Length	M	500, 1000, 2000							
Thickness	MM	0.08±	0.09±	0.09±	0.11 ±	0.12±	0.13±	0.14±	0.15±
		0.015	0.015	0.015	0.015	0.015	0.015	0.015	0.015
Weight of Tape	g/m ²	100±10	115±10	130±10	145±10	170±10	185±15	200±15	220±20
Weight of Paper	g/m ²	65±4	80±5	90±5	100±5	120±5	134±5	150±5	168±5
Weight of Class Cloth	g/m ²	21±2	28±2	28±2	28±2	28±2	28±2	28±2	28±2
Breakdown Voltage	KV	>1.2	>1.5	>1.5	>1.5	>1.6	>1.7	>1.8	>2.0
Tensile Strength	N/15mm	≥130	≥180	≥180	≥180	≥200	≥200	≥200	≥200
Binder Content	%	13±3	13±3	13±3	13±3	13±3	13±3	13±3	13±3
Mica Content	%	>60	>65	>65	>65	>65	>70	>70	>75
Fire Grades	°C	950—1000 IEC331							